



NSK 6216VV BALL BEARING

Bearing No. 6216VV

6216VV Bearing 2D drawings and 3D CAD models

Size	80x140x26 mm
Bore Diameter	80 mm
Outer Diameter	140 mm
Width	26 mm
d	80 mm
D	140 mm
B	26 mm
C	26 mm
r min.	2 mm
da min.	89 mm
da max	95,5 mm
Da max.	131 mm
ra max.	2 mm
Weight	1,42 Kg
Basic dynamic load rating (C)	72,5 kN
Basic static load rating (C0)	53 kN
(Grease) Lubrication Speed	4 500 r/min
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight / Kilogram	1.37
EAN	0029176015571
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0



Zhongjia Bearing Co. LTD

Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Non-Contact Seal
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	80MM Bore; 140MM Outside Diameter; 26MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.nskamericas.com
Manufacturer Item Number	6216VV
Weight / LBS	1.46
Outer Race Width	1.024 Inch 26 Millimeter
Outside Diameter	5.512 Inch 140 Millimeter
Bore	3.15 Inch 80 Millimeter
SRI	9.86
hidYobi	6216VV
LangID	1
D_	140
SREX	0.04
B_	26



Zhongjia Bearing Co. LTD

da min	89
hidTable	ecat_NS RDGB
SRE	9.86
mass	1.42
GRS rpm	4500
ra	2
SRIX	0.04
D_a	131
SRIN	-0.04
C0	53
fo	14.6
SREN	-0.04
DE_	129.05
Prod_Type3	DGBB_SR_VV
DA_	19.05
bomp	0
Z_	10
yobi	6216VV
C_conv	72500
ALPHA_	0
SDM_	110
r	2
KBRG	6151
SBRG	2
DI_	90.95